
P R O D U C T D A T A

15000
Fisheye Eliminator

DESCRIPTION:

15000 Fisheye Eliminator is a very effective additive for preventing fisheyes, craters, and other surface tension defects in the paint film caused by surface contamination. It is compatible with PC3v100, PC3 & PC4 Topcoats and PC3v100, PC3 & PC4 Clear Coats.

TECHNICAL DATA:

PACKAGED VOC	809 g/l, 6.75 lbs/gal
SHELF LIFE	one year (unopened)
FLASH POINT	102° F, 39° C
RECOMMENDED USE LEVEL	1 fluid ounce per gallon of activated Topcoat or Clear Coat

DIRECTIONS FOR USE: add up to 1 fluid ounce of 15000 Fisheye Eliminator per activated gallon of Topcoat or Clear Coat.

DISCLAIMER: The technical information and suggestions for use have been compiled for your guidance and usage. Such information is based on Precision Coatings, Inc. experience and research and is believed to be reliable. As PCI has no control over conditions in which the product is used, stored, or otherwise handled, the above information does not constitute a warranty. Buyers must assume responsibility for the suitability of the product for their purposes.

PRECISION COATINGS, INC. • 1940 E. TRAFFICWAY, SPRINGFIELD, MO 65802
PHONE (888) 340-6780 • FAX (888) 340-6783
EMAIL: precisioncoatingsinc.com

