

**SIGMACOVER CSF  
SPECIFIED USE PRODUCT ADDENDUM**

**5484 Addendum**

November 2006  
Revision of March 2004

**PRINCIPAL  
CHARACTERISTICS**

- Very low odor.
- Applies over power broomed steel deck. \*
- Insulation can be installed while coating is still wet
- No risk of solvent entrapment.
- Tested and approved for use to recoat roof decking exposed to phenolic insulation.

**EQUIPMENT RECOMMENDATION**

Listed below is **required** equipment for the application of CSF 5484. Recommendations are based on using Graco spray equipment (equivalent equipment may be used). Some accessories listed are not necessary but will greatly increase productivity.

**PUMPS**

GM 10000	
GH733	231-733
King 30:1	953-884
Bulldog 30:1	218-320

**GUNS**

Contractor Airless	220-955
Hydra Mastic	206-718

**ACCESSORIES**

Reverse-a-clean IV	222-674
Dual spray nozzle	206-236
Reverse-a-clean adaptor	181-085
24" extension	223-392
Reverse-a-clean IV tips	221-725 (14" fan)
	221-825 (16" fan)
Contractor gun filter	218-131

**CLEAN UP THINNER** 90-53 Preferred, 91-92 can be used within certain limits.

\* Power brooms must be outfitted with 100% wire bristles. Nylon bristles will not be accepted and the job will not be allowed to progress without wire brushes.

<b>GRACO</b>	Customer Service	1-800-328-0211
	Technical Service	1-800-543-0339

(11/06)